

Sludge Remover Bacteria Three Gram Pellets

ABB05X • ABB10X • ABB25X • ABB-50B



Features

EasyPro's family of water treatment products is designed to work together to achieve the natural ecological balance your pond needs to maintain clean, clear water.

Sludge Remover bacteria pellets are designed specifically to remove organic sludge from the bottom of lakes and ponds. Sludge is the result of fish waste, dead algae or plant material, uneaten fish food, leaves and other debris. The pellets, when introduced to the water, sink, dissolve and begin to remove bottom organic sludge — often several inches per year.

Simply toss pellets in the water for easy application!

- Diminishes bottom sludge buildup
- Removes pond odors caused by stagnant water and decaying material
- Sinking pellets for precise and effective placement when spot treating
- Enhances water clarity and reduces murky water caused by organic wastes
- Helps lower oxygen demand in the pond
- Reduces problem causing nitrate and phosphates
- Fish, family and animal safe

Directions for Use

For best results Sludge Remover pellets should be added every two weeks when water temperatures are above 55°F. Cold water strains will have effectiveness in water temperatures as low as 38°F.

Spot Treatments:

- Apply 1 scoop (8 oz.) per 1000-1500 square feet of beach, shoreline or problem area every two weeks

Full Pond Treatments:

- Broadcast two scoops per 1/4 acre of pond surface area every two weeks.

Avoid using copper based algaecides for 48 hours before applying.

KEEP OUT OF REACH OF CHILDREN

Safe for fish & aquatic life

Sizes

Part #	Description	Size	Treats Up To
ABB05X	Sludge Remover Bacteria Pellets, pail with scoop	5 lbs.	1.25 acres
ABB10X	Sludge Remover Bacteria Pellets, pail with scoop	10 lbs.	2.5 acres
ABB25X	Sludge Remover Bacteria Pellets, pail with scoop	25 lbs.	6.25 acres
ABB-50B	Sludge Remover Bacteria Pellets, box, no scoop	50 lbs.	12.5 acres



Ideal For

- Recreation ponds
- Ornamental ponds
- Aquaculture
- Retention ponds
- Farm ponds
- Irrigation ponds
- Golf course ponds
- Wastewater lagoons

When to Use

- Every two weeks spring, summer and fall

Parameters for Best Results

- Temperature:
Optimal 75°F, Range: 38°F - 100°F
- Dissolved Oxygen (DO):
>2 ppm, Minimum 1 ppm
- pH: Optimal 7, Range: 5.5 to 9.5